

Bright Cluster Manager 9.1

Machine Learning Manual

Revision: 280f4c2

Date: Mon Jan 25 2021



©2021 Bright Computing, Inc. All Rights Reserved. This manual or parts thereof may not be reproduced in any form unless permitted by contract or by written permission of Bright Computing, Inc.

Trademarks

Linux is a registered trademark of Linus Torvalds. PathScale is a registered trademark of Cray, Inc. Red Hat and all Red Hat-based trademarks are trademarks or registered trademarks of Red Hat, Inc. SUSE is a registered trademark of Novell, Inc. PGI is a registered trademark of NVIDIA Corporation. FLEXlm is a registered trademark of Flexera Software, Inc. PBS Professional, PBS Pro, and Green Provisioning are trademarks of Altair Engineering, Inc. All other trademarks are the property of their respective owners.

Rights and Restrictions

All statements, specifications, recommendations, and technical information contained herein are current or planned as of the date of publication of this document. They are reliable as of the time of this writing and are presented without warranty of any kind, expressed or implied. Bright Computing, Inc. shall not be liable for technical or editorial errors or omissions which may occur in this document. Bright Computing, Inc. shall not be liable for any damages resulting from the use of this document.

Limitation of Liability and Damages Pertaining to Bright Computing, Inc.

The Bright Cluster Manager product principally consists of free software that is licensed by the Linux authors free of charge. Bright Computing, Inc. shall have no liability nor will Bright Computing, Inc. provide any warranty for the Bright Cluster Manager to the extent that is permitted by law. Unless confirmed in writing, the Linux authors and/or third parties provide the program as is without any warranty, either expressed or implied, including, but not limited to, marketability or suitability for a specific purpose. The user of the Bright Cluster Manager product shall accept the full risk for the quality or performance of the product. Should the product malfunction, the costs for repair, service, or correction will be borne by the user of the Bright Cluster Manager product. No copyright owner or third party who has modified or distributed the program as permitted in this license shall be held liable for damages, including general or specific damages, damages caused by side effects or consequential damages, resulting from the use of the program or the un-usability of the program (including, but not limited to, loss of data, incorrect processing of data, losses that must be borne by you or others, or the inability of the program to work together with any other program), even if a copyright owner or third party had been advised about the possibility of such damages unless such copyright owner or third party has signed a writing to the contrary.

Table of Contents

Table of Contents	i
0.1 About This Manual	iii
0.2 About The Manuals In General	iii
0.3 Getting Administrator-Level Support	iii
0.4 Getting Professional Services	iv
1 Introduction And Machine Learning Packages Installation	1
1.1 Introduction	1
1.1.1 Bright Cluster Manager Versions—Associated Repositories And Support For Machine Learning Packages	1
1.1.2 Bright Cluster Manager Versions—Supported Distributions And Architecture For Machine Learning Packages	2
1.2 Available Packages	2
1.2.1 Considerations	6
1.3 Requirements	7
1.4 Machine Learning Packages Installation	7
1.4.1 Module Loading	9
1.5 Machine Learning Packages Removal	10
2 Running TensorFlow	13
2.1 Hello World	13
2.2 Convolutional Neural Network	14
2.3 Image Recognition	15
2.4 Iris Classification	15
3 Running PyTorch	17
3.1 Variational Autoencoders (VAEs)	17

Preface

Welcome to the *Machine Learning Manual* for Bright Cluster Manager 9.1.

0.1 About This Manual

This manual is aimed at helping cluster administrators install, understand, configure, and manage basic machine learning capabilities easily using Bright Cluster Manager. The administrator is expected to be reasonably familiar with the *Administrator Manual*.

0.2 About The Manuals In General

Regularly updated versions of the Bright Cluster Manager 9.1 manuals are available on updated clusters by default at `/cm/shared/docs/cm`. The latest updates are always online at <http://support.brightcomputing.com/manuals>.

- The *Installation Manual* describes installation procedures for a basic cluster.
- The *Administrator Manual* describes the general management of the cluster.
- The *User Manual* describes the user environment and how to submit jobs for the end user.
- The *Cloudbursting Manual* describes how to deploy the cloud capabilities of the cluster.
- The *Developer Manual* has useful information for developers who would like to program with Bright Cluster Manager.
- The *Edge Manual* describes how to deploy Bright Edge with Bright Cluster Manager.
- The *Machine Learning Manual*—this manual—describes how to install and configure machine learning capabilities with Bright Cluster Manager.

If the manuals are downloaded and kept in one local directory, then in most pdf viewers, clicking on a cross-reference in one manual that refers to a section in another manual opens and displays that section in the second manual. Navigating back and forth between documents is usually possible with keystrokes or mouse clicks.

For example: `<Alt>-<Backarrow>` in Acrobat Reader, or clicking on the bottom leftmost navigation button of xpdf, both navigate back to the previous document.

The manuals constantly evolve to keep up with the development of the Bright Cluster Manager environment and the addition of new hardware and/or applications. The manuals also regularly incorporate customer feedback. Administrator and user input is greatly valued at Bright Computing. So any comments, suggestions or corrections will be very gratefully accepted at manuals@brightcomputing.com.

There is also a feedback form available via Bright View, via the Account icon, , following the clickpath:

Account→Help→Feedback

0.3 Getting Administrator-Level Support

If the reseller from whom Bright Cluster Manager was bought offers direct support, then the reseller should be contacted.

Otherwise the primary means of support is via the website <https://support.brightcomputing.com>. This allows the administrator to submit a support request via a web form, and opens up a trouble ticket. It is a good idea to try to use a clear subject header, since that is used as part of a reference tag as the ticket progresses. Also helpful is a good description of the issue. The followup communication for this ticket goes via standard e-mail. Section 17.2 of the *Administrator Manual* has more details on working with support.

0.4 Getting Professional Services

Bright Computing normally differentiates between professional services (customer asks Bright Computing to do something or asks Bright Computing to provide some service) and support (customer has a question or problem that requires an answer or resolution). Professional services can be provided after consulting with the reseller, or the Bright account manager.

1

Introduction And Machine Learning Packages Installation

1.1 Introduction

From Bright Cluster Manager version 7.3 onward, a number of machine learning and deep learning library and framework packages can be used. The packages provided make it faster and easier for organizations to install the latest state-of-the-art libraries, and gain insights from rich, complex data.

1.1.1 Bright Cluster Manager Versions—Associated Repositories And Support For Machine Learning Packages

- In Bright Cluster Manager versions 7.3 and 8.0 the machine learning and deep learning packages are experimentally accessible to a cluster from the standard Bright cm repository. However, from Bright Cluster Manager version 8.1 onward, these packages are distributed via a separate Bright cm-ml repository.
- In Bright Cluster Manager versions 8.1 and 8.2, cluster administrators have to activate the Data Science Add-on using the online wizard at:

<http://licensing.brightcomputing.com/licensing/activate-data-science/>

The add-on enables the dedicated Bright cm-ml repository.

- From Bright Cluster Manager version 9.0 onward the activation step via a wizard is not needed—the repository is automatically available and enabled.

Only if the cluster is licensed for the Data Science Add-on package does Bright provide support for the integration of packages distributed in the dedicated repository with Bright Cluster Manager.

For convenience, a summary of the Bright for Data Science (B4DS) repository configuration requirements is shown in table 1.1:

Table 1.1: Bright Cluster Manager offering overview for Machine Learning packages

Bright CM	Packages repository	Repository configuration	Support
7.3	Traditional (cm)	Automatically available and enabled	Not available
8.0	Traditional (cm)	Automatically available and enabled	Not available
8.1	Dedicated (cm-ml)	Requires B4DS Add-on activation*	Requires B4DS Add-on
8.2	Dedicated (cm-ml)	Requires B4DS Add-on activation*	Requires B4DS Add-on
9.0	Dedicated (cm-ml)	Automatically available and enabled	Requires B4DS Add-on
9.1	Dedicated (cm-ml)	Automatically available and enabled	Requires B4DS Add-on

* Activation is via <http://licensing.brightcomputing.com/licensing/activate-data-science/>

An administrator who is upgrading a cluster that has machine learning and deep learning packages installed on it should always make sure that the dedicated Bright cm-ml repository is accessible, if required by the new Bright Cluster Manager version.

1.1.2 Bright Cluster Manager Versions—Supported Distributions And Architecture For Machine Learning Packages

At the time of writing, October 2020, a number of different Linux distribution versions and architectures are supported, depending on the Bright Cluster Manager version. For convenience, a support matrix for this is shown in table 1.2:

Table 1.2: Supported Linux distributions and architectures for Bright Machine Learning packages

Bright CM	Architectures	Linux distributions
7.3	x86_64	CentOS 7, RHEL 7, SLES 12
8.0	x86_64	CentOS 7, RHEL 7, SLES 12
8.1	x86_64	CentOS 7, RHEL 7, SLES 12
8.2	x86_64	CentOS 7, RHEL 7, SLES 12, Ubuntu 18.04
9.0	x86_64	CentOS 7, CentOS 8, RHEL 7, RHEL 8, SLES 12, SLES 15, Ubuntu 18.04
9.1	x86_64	CentOS 7, CentOS 8, RHEL 7, RHEL 8, SLES 12, SLES 15, Ubuntu 18.04

An updated list of the supported Linux distributions and architectures available for the various Bright Cluster Manager versions can be found at <https://support.brightcomputing.com/feature-matrix/>, in the section of the Feature column dedicated to machine learning.

1.2 Available Packages

An updated list of the machine learning packages available for the various Bright Cluster Manager versions can be found at <https://support.brightcomputing.com/packages-dashboard/>. Most of the machine learning packages are to be found within the ml group. However, some of them are found within the cm group for legacy reasons.

At the time of writing, October 2020, the following packages were available:

Table 1.3: Machine Learning packages provided by the Bright Cluster Manager repositories

Package name	Description
cm-bazel	An open-source build and test tool similar to Make, Maven, and Gradle. It uses a human-readable, high-level build language. Bazel supports projects in multiple languages and builds outputs for multiple platforms.
cm-chainer-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A flexible framework for neural networks, designed to write complex architectures simply and intuitively.
cm-cub-cuda10.2 (C7, C8, R7, R8, S2, S5, U8)	A flexible library of cooperative threadblock primitives and other utilities for CUDA kernel programming.
cm-dynet-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A neural network library developed by Carnegie Mellon University and many others. It is written in C++ (with bindings in Python) and is designed to be efficient when run on either CPU or GPU, and to work well with networks that have dynamic structures that change for every training instance.
cm-fastai-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A library that simplifies training fast and accurate neural nets using modern best practices.
cm-gpytorch-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A Gaussian process library implemented using PyTorch.
cm-horovod-mxnet-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A distributed training framework for TensorFlow, Keras, PyTorch, and MXNet.
cm-horovod-pytorch-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A distributed training framework for TensorFlow, Keras, PyTorch, and MXNet.
cm-horovod-tensorflow-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A distributed training framework for TensorFlow, Keras, PyTorch, and MXNet.
cm-horovod-tensorflow2-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A distributed training framework for TensorFlow, Keras, PyTorch, and MXNet.

...continues

Table 1.3: Machine Learning Packages Included...continued

Package name	Description
cm-keras-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A high-level neural networks Python API, capable of running on top of TensorFlow, CNTK, or Theano. It was developed with a focus on enabling fast experimentation.
cm-keras-py37-mkl-gcc8 (C7, C8, R7, R8, S2, S5, U8)	A high-level neural networks Python API, capable of running on top of TensorFlow, CNTK, or Theano. It was developed with a focus on enabling fast experimentation.
cm-ml-distdeps-cuda10.2 (C7, C8, R7, R8, S2, S5, U8)	Meta-package containing distribution-specific dependencies for machine learning frameworks.
cm-ml-distdeps-mkl (C7, C8, R7, R8, S2, S5, U8)	Meta-package containing distribution-specific dependencies for machine learning frameworks.
cm-ml-pythondeps-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	Meta-package containing Python dependencies for machine learning frameworks. It includes, for example, NumPy, PyCUDA, pandas, NetworkX, pydot and Matplotlib.
cm-ml-pythondeps-py37-mkl-gcc8 (C7, C8, R7, R8, S2, S5, U8)	Meta-package containing Python dependencies for machine learning frameworks. It includes, for example, NumPy, PyCUDA, pandas, NetworkX, pydot and Matplotlib.
cm-mxnet-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A deep learning framework designed for both efficiency and flexibility. It allows a mix of symbolic and imperative programming and contains a dynamic dependency scheduler that automatically parallelizes any operations on the fly.
cm-nccl2-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	Version 2 of NCCL, an implementation of multi-GPU and multi-node collective communication primitives that are performance optimized for NVIDIA GPUs.
cm-onnx-pytorch-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	An open format built to represent machine learning models.
cm-onnx-tensorflow-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	An open format built to represent machine learning models.
cm-open3d-py37-cuda10.2-gcc (C7, R7, S2, S5)	An open-source library that supports rapid development of software that deals with 3D data.
cm-opencv3-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	An open-source BSD-licensed library that includes several hundreds of computer vision algorithms.

...continues

Table 1.3: Machine Learning Packages Included...continued

Package name	Description
cm-opencv3-py37-mkl-gcc8 (C7, C8, R7, R8, S2, S5, U8)	An open-source BSD-licensed library that includes several hundreds of computer vision algorithms.
cm-protobuf3-gcc (C7, C8, R7, R8, S2, S5, U8)	Version 3 of Protocol Buffers, a language-neutral, platform-neutral extensible mechanism for serializing structured data.
cm-protobuf3-gcc8 (C7, C8, R7, R8, S2, S5, U8)	Version 3 of Protocol Buffers, a language-neutral, platform-neutral extensible mechanism for serializing structured data.
cm-pytorch-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	An optimized tensor library for deep learning using GPUs and CPUs. It provides tensor computation (like NumPy) with strong GPU acceleration, and deep neural networks built on a tape-based autograd system. It now includes Caffe2.
cm-tensorflow-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	An open source software library for numerical computation using data flow graphs originally developed by researchers and engineers working on the Google Brain team.
cm-tensorflow-py37-mkl-gcc8 (C7, C8, R7, R8, S2, S5, U8)	An open source software library for numerical computation using data flow graphs originally developed by researchers and engineers working on the Google Brain team.
cm-tensorflow2-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	An open source software library for numerical computation using data flow graphs originally developed by researchers and engineers working on the Google Brain team.
cm-tensorrt-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A platform for high-performance deep learning inference designed by NVIDIA and built on CUDA. It includes a deep learning inference optimizer and runtime that delivers low latency and high-throughput for deep learning inference applications.
cm-theano-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	A Python library that allows you to define, optimize, and evaluate mathematical expressions involving multi-dimensional arrays efficiently.
cm-xgboost-py37-cuda10.2-gcc (C7, C8, R7, R8, S2, S5, U8)	An optimized distributed gradient boosting library designed to be highly efficient, flexible and portable. It implements machine learning algorithms under the gradient boosting framework.

Legend:

C7: CentOS 7

C8: CentOS 8

R7: RHEL 7

R8: RHEL 8

S2: SLES 12

...continues

Table 1.3: Machine Learning Packages Included...continued

Package name	Description
S5: SLES 15	
U8: Ubuntu 18.04	
Package are available for every distribution unless otherwise tagged.	
Examples:	
	<code>cm-bazel</code> is available for every distribution.
	<code>cm-chainer-py37-cuda10.1-gcc (R7)</code> is only available for RHEL7.

1.2.1 Considerations

There are some considerations that the cluster administrator should be aware of with the packages.

- Some packages may be labelled in the table 1.3 as deprecated. “Deprecated” in the software industry is not a well-defined term. Here it is used by Bright Computing to mean a package that may no longer be offered in a future release, or for which a newer existing version is preferred.
- Several different packages may be provided for the same machine learning library or framework. For example, TensorFlow may be provided by:
 - `cm-tensorflow-py36-cuda10.1-gcc` or
 - `cm-tensorflow-py37-mkl-gcc8`

As is the norm with other package management systems in the software industry, the name given to a Bright Computing package includes the most relevant dependencies required to build and use it. The dependencies commonly highlighted in this manner are:

- Python interpreter version used (e.g. `*-py36*` and `*-py37*`)
- accelerator library used (e.g. `*-cuda10.1*` and `*-mkl*`)
- compiler used (e.g. `*-gcc*` and `*-gcc8*`)

The availability of different variants of the same package makes it easier for administrators to set up a working environment that is suited to their needs.

- Machine learning packages are designed to coexist, and can therefore all be installed at the same time. This also applies to different variants of the same library or framework.

This means that administrators can install different versions of the same machine learning library or framework, simply by using different variants. For example: an older `*-py36*` version of TensorFlow, as well as a more recent `*-py37*` version of TensorFlow, can both be installed at the same time.

- As is done with other packages provided by Bright Computing, the updates released for machine learning libraries and frameworks generally leave their major versions unchanged.

Whenever a major version for a third party machine learning library or a framework is publicly released, a new package or a set of packages is typically placed in the repository.

Such package(s) imply or contain a reference to the major version in the name. For example:

- `cm-tensorflow-*` is the name used for TensorFlow major version 1
- `cm-tensorflow2-*` is the name for TensorFlow major version 2

As a result, administrators can safely upgrade cluster packages without breaking backward compatibility with users’ applications.

- MPI modules and libraries should not be blindly added by the cluster administrator. During module loading, warnings are typically given to suggest an MPI library (Open MPI, or an MPICH or MVAPICH implementation of Open MPI) is required. However, the exact implementation of the MPI library that can be used depends upon the hardware (GPU, interface, architecture) used and requires judgment of suitability by the cluster administrator. Bright Cluster Manager uses the `cm-openmpi-geib-cuda10.1-gcc` package in this manual as the reference MPI library implementation. This driver package corresponds with using Open MPI with Gigabit Ethernet and InfiniBand networking, NVIDIA GPUs, and x86 architecture.

1.3 Requirements

The following requirements must be met before installing the preceding machine learning packages.

- RHEL users must have access to the YUM repositories and EPEL repository.
- There must be enough free space for the packages that are installed on the head node and compute nodes. The actual amount depends on the packages installed.
- 8 GB of RAM on the nodes is the minimum recommended amount.
- In order to use packages built with the CUDA toolkit accelerator library (i.e. `*-cuda*`), the NVIDIA GPUs must be Maxwell or more recent, with compute capability 3.5 or later. CUDA compute capability 6.0 or later is recommended.
- In order to use packages built with GCC 5 as compiler (i.e. `*-gcc`), the CPU must support the AVX/AVX2, FMA, and SSE4.2 instructions. This can be checked by inspecting the CPU flags:

Example

```
[root@node ~]# egrep -m1 -o '(avx|avx2|fma|sse4_2)' /proc/cpuinfo
fma
sse4_2
avx
avx2
```

- In order to use packages built using MKL as the accelerator (i.e. `*-mkl`), the CPU must support the AVX-512 Vector Neural Network Instructions (VNNI). Examples of such CPUs are Intel Xeon Scalable processors with Deep Learning Boost.

1.4 Machine Learning Packages Installation

Head Node Installation

Bright Cluster Manager machine learning packages are installed in the `/cm/shared` directory, which is by default exported over NFS. Packages installed on the head node are therefore also available to all the compute nodes by default.

The `.rpm` and `.deb` files have proper dependencies defined. This means that the cluster administrator does not need to spend time figuring out what needs to be installed to set up a working environment. Whenever a package is installed or updated, the required dependencies will be also automatically fetched, if necessary. As a result, packages can be installed with the usual package manager that is provided by the Linux distribution in the usual way (page 457 of the *Administrator Manual*).

For example, the administrator can install `cm-pytorch-py36-cuda10.1-gcc` as follows:

Example

```
[root@bright91 ~]# yum install cm-pytorch-py36-cuda10.1-gcc      #on RHEL 7
[root@bright91 ~]# zypper install cm-pytorch-py36-cuda10.1-gcc  #on SLES 15
[root@bright91 ~]# apt-get install cm-pytorch-py36-cuda10.1-gcc #on Ubuntu 18.04
```

The package managers also automatically install the corresponding dependencies, such as

- `cm-ml-distdeps-cuda10.1`
- `cm-ml-pythondeps-py36-cuda10.1-gcc`
- `cm-protobuf3-gcc`
- `cuda10.1-toolkit`
- `cm-cudnn7.6-cuda10.1`
- `cm-nccl2-cuda10.1-gcc`

Machine learning packages share several dependencies, usually providing useful Python or system libraries. For convenience, these dependencies are grouped in the `cm-ml-pythondeps-*` and `cm-ml-distdeps-*` meta-packages.

- `cm-ml-pythondeps-*`: This meta-package provides the application libraries such as `numba`, `numpy`, `scikit-learn`, and `scipy`.
- `cm-ml-distdeps-*`: This meta-package, on the other hand, provides development libraries such as `blas-devel`, `libjpeg-devel` and `libpng-devel`, and the utility library `gnuplot`.

The appropriate meta-packages are automatically installed whenever a package installation requires it.

Administrators only need to make sure that their clusters meet the preceding hardware requirements listed at the start of section 1.3. If that is not done, then unexpected failures may occur during run time, such as segmentation faults.

Examples of common mistakes are

- installing packages requiring CUDA (e.g. `cm-pytorch-py36-cuda10.1-gcc`) on clusters without GPUs
- installing packages requiring VNNI (e.g. `cm-tensorflow-py36-mkl-gcc8`) on CPUs not supporting the instruction set

Compute Nodes Installation

The `cm-ml-distdeps-*` meta-packages must be also installed onto all compute nodes that are to run machine learning applications.

For example, if the name of the software image is `gpu-image`, then the administrator can install `cm-ml-distdeps-cuda10.1` on RHEL 7 as follows:

Example

```
[root@bright91 ~]# yum install --installroot=/cm/images/gpu-image cm-ml-distdeps-cuda10.1
```

The preceding command must be applied to all software images that are used to run machine learning applications.

There are equivalents to the `--installroot` option of `yum` for the other distribution package managers.

For SLES the installation command equivalent is:

```
[root@bright91 ~]# zypper --root /cm/images/gpu-image install cm-ml-distdeps-cuda10.1
```

For Ubuntu the installation command equivalent is:

```
[root@bright91 ~]# cm-chroot-sw-img /cm/images/gpu-image
[root@bright91 ~]# apt install cm-ml-distdeps-cuda10.1
[root@bright91 ~]# exit      #get out of chroot
```

Details on using zypper and apt commands for installation to software images are given on page 12.2.1 of the *Administrator Manual*.

The preceding command must be applied to all software images that are used to run machine learning applications.

1.4.1 Module Loading

Bright Cluster Manager provides environment module definitions for all the machine learning packages. The environment module files are also compatible with the Lmod software introduced in Bright Cluster Manager 7.3. They can be listed once the shared module is loaded, if it has not already been loaded:

```
[root@bright91 ~]# module purge; module available
----- /cm/local/modulefiles -----
cluster-tools/9.0      cmd   freeipmi/1.6.4   luajit      openldap
cm-image/9.0          cmjob gcc/9.2.0        module-git  python3
cm-scale/cm-scale.module cmsh  ipmitool/1.8.18 module-info python37
cm-setup/9.0          dot   lua/5.3.5        null        shared
[root@bright91 ~]# module load shared; module available
----- /cm/local/modulefiles -----
cluster-tools/9.0      cmd   freeipmi/1.6.4   luajit      openldap
cm-image/9.0          cmjob gcc/9.2.0        module-git  python3
cm-scale/cm-scale.module cmsh  ipmitool/1.8.18 module-info python37
cm-setup/9.0          dot   lua/5.3.5        null        shared

----- /cm/shared/modulefiles -----
blacs/openmpi/gcc/64/1.1patch03  hpl/2.2
blas/gcc/64/3.8.0                hwloc/1.11.11
bonnie++/1.98                    intel-tbb-oss/ia32/2019_20191006oss
cm-image/master                  intel-tbb-oss/intel64/2019_20191006oss
cm-pmix3/3.1.4                   iozone/3_487
cuda10.1/blas/10.1.243           keras-py36-cuda10.1-gcc/2.3.1
cuda10.1/fft/10.1.243            lapack/gcc/64/3.8.0
cuda10.1/nsight/10.1.243         ml-pythondeps-py36-cuda10.1-gcc/3.0.0
cuda10.1/profiler/10.1.243       mpich/ge/gcc/64/3.3
cuda10.1/toolkit/10.1.243        mvapich2/gcc/64/2.3
cudnn7.6-cuda10.1/7.6.5.32       ncc12-cuda10.1-gcc/2.4.8
default-environment              netcdf/gcc/64/4.6.1
fftw2/openmpi/gcc/64/double/2.1.5 netperf/2.7.0
fftw2/openmpi/gcc/64/float/2.1.5 openblas/dynamic/(default)
fftw3/openmpi/gcc/64/3.3.8       openblas/dynamic/0.2.20
gcc5/5.5.0                       openmpi/gcc/64/1.10.7
gdb/8.3.1                         protobuf3-gcc/3.10.1
globalarrays/openmpi/gcc/64/5.7  scalapack/openmpi/gcc/64/2.0.2
 hdf5/1.10.1                      tensorflow-py36-cuda10.1-gcc/1.14.0
 hdf5_18/1.8.20                   ucx/1.6.1
```

For example, after having installed the `cm-tensorflow-py36-cuda10.1-gcc` package, the associated TensorFlow module can be loaded with:

```
[root@bright91 ~]# module load tensorflow-py36-cuda10.1-gcc
Loading tensorflow-py36-cuda10.1-gcc/1.14.0
Loading requirement: gcc5/5.5.0 python36 cuda10.1/toolkit/10.1.243
ml-pythondeps-py36-cuda10.1-gcc/3.0.0 openblas/dynamic/0.2.20 cudnn7.6-cuda10.1/7.6.5.32
hdf5_18/1.8.20 keras-py36-cuda10.1-gcc/2.3.1 nccl2-cuda10.1-gcc/2.4.8
```

The machine learning environment modules automatically load additional environment modules as dependencies, with the notable exception of Open MPI implementations for the reasons given in section 1.2.1.

The module dependencies are achieved via the module definition files:

Example

```
[root@bright91 ~]# module show tensorflow-py36-cuda10.1-gcc
-----
/cm/shared/modulefiles/tensorflow-py36-cuda10.1-gcc/1.15.2:

module-whatismodule adds TensorFlow to your environment variables
module load ml-pythondeps-py36-cuda10.1-gcc
module load keras-py36-cuda10.1-gcc
module load cuda10.1/toolkit
module load openblas
module load protobuf3-gcc
module load cudnn7.6-cuda10.1
module load hdf5_18
module load nccl2-cuda10.1-gcc
module load gcc5
prepend-path PYTHONPATH /cm/shared/apps/tensorflow-py36-cuda10.1-gcc/1.15.2/lib/python3.6/site-packages/
prepend-path PYTHONPATH /cm/shared/apps/tensorflow-py36-cuda10.1-gcc/1.15.2/lib64/python3.6/site-packages/
prepend-path LD_LIBRARY_PATH /cm/shared/apps/tensorflow-py36-cuda10.1-gcc/1.15.2/lib/python3.6/\
site-packages/tensorflow_core
prepend-path LD_LIBRARY_PATH /cm/shared/apps/tensorflow-py36-cuda10.1-gcc/1.15.2/lib/python3.6/\
site-packages/tensorflow_core/include
prepend-path LD_LIBRARY_PATH /cm/shared/apps/tensorflow-py36-cuda10.1-gcc/1.15.2/lib64/python3.6/\
site-packages/tensorflow_core
prepend-path LD_LIBRARY_PATH /cm/shared/apps/tensorflow-py36-cuda10.1-gcc/1.15.2/lib64/python3.6/\
site-packages/tensorflow_core/include
prepend-path PATH /cm/shared/apps/tensorflow-py36-cuda10.1-gcc/1.15.2/bin
-----
```

1.5 Machine Learning Packages Removal

Machine learning packages can be removed in the usual way with the package manager commands used by the Linux distribution. For example, the administrator can remove the `cm-pytorch-py36-cuda10.1-gcc` package with:

Example

```
[root@bright91 ~]# yum remove cm-pytorch-py36-cuda10.1-gcc #on RHEL 7

or

[root@bright91 ~]# zypper remove cm-pytorch-py36-cuda10.1-gcc #on SLES 15

or

[root@bright91 ~]# apt-get remove cm-pytorch-py36-cuda10.1-gcc #on Ubuntu 18.04
```


Bright Cluster Manager machine learning packages are installed in the `/cm/shared` directory, which is by default exported over NFS. Packages removed from the head node are therefore also removed from all the compute nodes by default.

The `cm-ml-distdeps-*` meta-packages must be also removed from all compute nodes that are to run machine learning applications. For example, if the name of the software image is `gpu-image`, then the images directory is `/cm/images/gpu-image`, and then the administrator can remove `cm-ml-distdeps-cuda10.1` from the image as follows in RHEL 7:

Example

```
[root@bright91 ~]# yum remove --installroot=/cm/images/gpu-image cm-ml-distdeps-cuda10.1
```

The preceding command must be applied to all software images that are used to run the machine learning applications.

The equivalents to the `--installroot` option of `yum` for the other distribution package managers are described in section 1.4.

2

Running TensorFlow

This chapter goes through some example runs with TensorFlow. Some output messages have been removed in the runs for readability.

It assumes TensorFlow has been installed, with, for example, `yum install cm-tensorflow-py36-cuda10.1-gcc`.

In addition, TensorFlow requires an OpenMPI implementation to work. As described in Chapter 3 of the *User Manual*, the Bright repositories provide different OpenMPI packages. This allows the user to choose which one to use, depending on, for example, which interconnect is being used, or if CUDA support is required.

In this chapter, the `cm-openmpi-geib-cuda10.1-gcc` package is used.

2.1 Hello World

A “Hello World” interactive example that just shows that the software is in place for TensorFlow can be run as follows:

Example

```
[root@bright91 ~]# module load shared
[root@bright91 ~]# module load tensorflow-py36-cuda10.1-gcc
[root@bright91 ~]# module load openmpi-geib-cuda10.1-gcc
[root@bright91 ~]# python3.6
Python 3.6.9 (default, Nov 20 2019, 21:00:07)
[GCC 4.8.5 20150623 (Red Hat 4.8.5-28)] on linux
Type "help", "copyright", "credits" or "license" for more information.
>>> import tensorflow as tf

>>> hello = tf.constant('Hello, TensorFlow!')
>>> sess = tf.Session()

name: Tesla K40c major: 3 minor: 5 memoryClockRate(GHz): 0.745
pciBusID: 0000:00:08.0
totalMemory: 11.17GiB freeMemory: 11.09GiB

>>> sess.run(hello)
b'Hello, TensorFlow!'
>>> a = tf.constant(10)
>>> b = tf.constant(32)
>>> sess.run(a+b)
42
>>>
```

2.2 Convolutional Neural Network

The following trains a convolutional neural network similar to LeNet-5.

The code uses the TensorFlow convolutional module at `/cm/shared/apps/tensorflow-py36-cuda10.1-gcc/current/models/tutorials/image/mnist/convolutional.py`.

It picks up training images and labels from the MNIST site, and places them in a directory `data` if it needs to. The images are then used to train and validate the model. End users would be expected to train the neural network within their home directories.

Example

```
[root@bright91 ~]# module load tensorflow-py36-cuda10.1-gcc
[root@bright91 ~]# module load openmpi-geib-cuda10.1-gcc
[root@bright91 ~]# cd /cm/shared/apps/tensorflow-py36-cuda10.1-gcc/current/models/\
tutorials/image/mnist/
[root@bright91 mnist]# python convolutional.py
Successfully downloaded train-images-idx3-ubyte.gz 9912422 bytes.
Successfully downloaded train-labels-idx1-ubyte.gz 28881 bytes.
Successfully downloaded t10k-images-idx3-ubyte.gz 1648877 bytes.
Successfully downloaded t10k-labels-idx1-ubyte.gz 4542 bytes.
Extracting data/train-images-idx3-ubyte.gz
Extracting data/train-labels-idx1-ubyte.gz
Extracting data/t10k-images-idx3-ubyte.gz
Extracting data/t10k-labels-idx1-ubyte.gz

2018-05-02 13:37:08.796152: I tensorflow/core/common_runtime/gpu/gpu_device.cc:1344] \
  Found device 0 with properties:
name: Tesla K40c major: 3 minor: 5 memoryClockRate(GHz): 0.745
pciBusID: 0000:00:08.0
totalMemory: 11.17GiB freeMemory: 11.09GiB
Initialized!

Step 0 (epoch 0.00), 25.9 ms
Minibatch loss: 8.334, learning rate: 0.010000
Minibatch error: 85.9%
Validation error: 84.6%
Step 100 (epoch 0.12), 158.8 ms
Minibatch loss: 3.267, learning rate: 0.010000
Minibatch error: 7.8%
Validation error: 7.5%
Step 200 (epoch 0.23), 154.9 ms
Minibatch loss: 3.355, learning rate: 0.010000
Minibatch error: 9.4%
...
Validation error: 0.8%
Step 8400 (epoch 9.77), 160.8 ms
Minibatch loss: 1.595, learning rate: 0.006302
Minibatch error: 0.0%
Validation error: 0.8%
Step 8500 (epoch 9.89), 157.6 ms
Minibatch loss: 1.611, learning rate: 0.006302
Minibatch error: 0.0%
Validation error: 0.9%
Test error: 0.7%
[root@bright91 ~]#
```

2.3 Image Recognition

The following session shows a pre-trained model running the `classify_image.py` script to recognize a test image of a panda:

Example

```
[root@bright91 ~]# module load tensorflow-py36-cuda10.1-gcc
[root@bright91 ~]# module load openmpi-geib-cuda10.1-gcc
[root@bright91 ~]# cd /cm/shared/apps/tensorflow-py36-cuda10.1-gcc/current/models/\
tutorials/image/imagenet
[root@bright91 imagenet]# python classify_image.py --image_file cropped_panda.jpg
2018-05-02 18:03:05.773697: I tensorflow/core/common_runtime/gpu/gpu_device.cc:1344] \
  Found device 0 with properties:
name: Tesla K40c major: 3 minor: 5 memoryClockRate(GHz): 0.745
pciBusID: 0000:00:08.0
totalMemory: 11.17GiB freeMemory: 11.09GiB
>> Downloading inception-2015-12-05.tgz 100.0%
Successfully downloaded inception-2015-12-05.tgz 88931400 bytes.
2018-05-02 18:03:06.725257: W tensorflow/core/framework/op_def_util.cc:343] Op Batch\
NormWithGlobalNormalization is deprecated. It will cease to work in GraphDef version\
  9. Use tf.nn.batch_normalization().
giant panda, panda, panda bear, coon bear, Ailuropoda melanoleuca (score = 0.89107)
indri, indris, Indri indri, Indri brevicaudatus (score = 0.00779)
lesser panda, red panda, panda, bear cat, cat bear, Ailurus fulgens (score = 0.00296)
custard apple (score = 0.00147)
earthstar (score = 0.00117)
[root@bright91 imagenet]#
```

2.4 Iris Classification

The iris flower data set is a standard raw data set, originally measured by R. A. Fisher in 1936. The data values in the set are a list of, per flower, the petal length and width, and the sepal length and width. Sepals are leaflike "under petals" under the actual petals. Based on these 4 attributes per flower, the fifth attribute—the species that the iris flower belongs to—can be determined. The determination of the species does not have an obvious solution because it depends on multiple variables at the same time. Fisher came up with a mathematical method to determine the species.

In machine learning, the iris flower data set is commonly used to illustrate concepts. An iris classification program, `premade_estimator`, is therefore a core TensorFlow program. The following session shows a run with `premade_estimator`, which downloads the data values used for training if required (some output ellipsized or removed for clarity):

```
[root@bright91 ~]# module load tensorflow-py36-cuda10.1-gcc
[root@bright91 ~]# module load openmpi-geib-cuda10.1-gcc
[root@bright91 ~]# cd /cm/shared/apps/tensorflow-py36-cuda10.1-gcc/current/models/samples/\
core/get_started
[root@bright91 get_started]# python premade_estimator.py
Downloading data from http://download.tensorflow.org/data/iris_training.csv
16384/2194 [===== 0s 0us/step
Downloading data from http://download.tensorflow.org/data/iris_test.csv
16384/573 [===== 0s 0us/step
INFO:tensorflow:Using default config.
WARNING:tensorflow:Using temporary folder as model directory: /tmp/tmpLqap1u
INFO:tensorflow:Using config: '_save_checkpoints_secs': 600, ' ...'_save_summary_steps': 100
INFO:tensorflow:Calling model_fn.
INFO:tensorflow:Done calling model_fn.
```

```
INFO:tensorflow:Create CheckpointSaverHook.
INFO:tensorflow:Graph was finalized.
2018-05-02 15:50:53.815952: I tensorflow/co...Found device 0 with properties:
name: Tesla K40c major: 3 minor: 5 memoryClockRate(GHz): 0.745
pciBusID: 0000:00:08.0
totalMemory: 11.17GiB freeMemory: 11.09GiB
INFO:tensorflow:Running local_init_op.
INFO:tensorflow:Done running local_init_op.
INFO:tensorflow:Saving checkpoints for 1 into /tmp/tmpLqap1u/model.ckpt.
INFO:tensorflow:loss = 192.68596, step = 1
INFO:tensorflow:global_step/sec: 468.658
INFO:tensorflow:loss = 12.971608, step = 101 (0.214 sec)
INFO:tensorflow:global_step/sec: 685.834
...
INFO:tensorflow:loss = 4.189755, step = 901 (0.158 sec)
INFO:tensorflow:Saving checkpoints for 1000 into /tmp/tmpLqap1u/model.ckpt.
INFO:tensorflow:Loss for final step: 6.7716765.
INFO:tensorflow:Calling model_fn.
INFO:tensorflow:Done calling model_fn.
INFO:tensorflow:Starting evaluation at 2018-05-02-13:50:58
INFO:tensorflow:Graph was finalized.
INFO:tensorflow:Restoring parameters from /tmp/tmpLqap1u/model.ckpt-1000
INFO:tensorflow:Running local_init_op.
INFO:tensorflow:Done running local_init_op.
INFO:tensorflow:Finished evaluation at 2018-05-02-13:50:58
INFO:tensorflow:Saving dict for global step 1000: accuracy = 0.96666664,...loss = 1.6617917
```

Test set accuracy: 0.967

```
INFO:tensorflow:Calling model_fn.
INFO:tensorflow:Done calling model_fn.
INFO:tensorflow:Graph was finalized.
INFO:tensorflow:Restoring parameters from /tmp/tmpLqap1u/model.ckpt-1000
INFO:tensorflow:Running local_init_op.
INFO:tensorflow:Done running local_init_op.
```

Prediction is "Setosa" (99.9%), expected "Setosa"

Prediction is "Versicolor" (99.5%), expected "Versicolor"

Prediction is "Virginica" (97.7%), expected "Virginica"

More information on the program can be found at <https://www.tensorflow.org/tutorials/quickstart/beginner>.

3

Running PyTorch

This chapter goes through some example runs with PyTorch. Some output messages have been removed in the runs for readability.

It assumes PyTorch has been installed with a package manager from the Bright Cluster Manager repository. For example with:

```
yum install cm-pytorch-py36-cuda10.1-gcc
```

In addition, PyTorch requires an OpenMPI implementation to work. As described in Chapter 3 of the *User Manual*, the Bright repositories provide different OpenMPI packages. This allows the user to choose which one to use, depending on, for example, which interconnect is being used, or if CUDA support is required.

In this chapter, the `cm-openmpi-geib-cuda10.1-gcc` package is used.

3.1 Variational Autoencoders (VAEs)

The following example shows how to train *Variational Autoencoders*¹, powerful generative models that can be used for a wide variety of applications.

The source code is available in the official PyTorch GitHub repository and can be fetched as follows:

```
[root@bright91 ~]# git clone https://github.com/pytorch/examples.git
[root@bright91 ~]# cd examples/
[root@bright91 ~]# git checkout 6c51ca5a614cfdbdcd4e8c3e70321c5f6defb177
[root@bright91 ~]# cd vae/
```

The Variational Autoencoders network is trained by default for 10 epochs. The required dataset can automatically be downloaded and extracted with:

Example

```
[root@bright91 ~]# module load shared
[root@bright91 ~]# module load pytorch-py36-cuda10.1-gcc
[root@bright91 ~]# module load openmpi-geib-cuda10.1-gcc
[root@bright91 ~]# python3.6 main.py
Downloading http://yann.lecun.com/exdb/mnist/train-images-idx3-ubyte.gz to
../data/MNIST/raw/train-images-idx3-ubyte.gz
9920512it [00:04, 2041116.37it/s]
Extracting ../data/MNIST/raw/train-images-idx3-ubyte.gz to ../data/MNIST/raw
...
Processing...
Done!
```

¹Original paper: "Auto-Encoding Variational Bayes" by Diederik P Kingma and Max Welling; <https://arxiv.org/abs/1312.6114>.

```
Train Epoch: 1 [0/60000 (0%)] Loss: 550.187805
Train Epoch: 1 [1280/60000 (2%)] Loss: 323.104736
Train Epoch: 1 [2560/60000 (4%)] Loss: 237.460938
...
Train Epoch: 1 [58880/60000 (98%)] Loss: 130.540909
====> Epoch: 1 Average loss: 164.1742
====> Test set loss: 127.8219
Train Epoch: 2 [0/60000 (0%)] Loss: 127.949753
...
Train Epoch: 10 [58880/60000 (98%)] Loss: 107.980888
====> Epoch: 10 Average loss: 106.1472
====> Test set loss: 105.8715
```

The output sampled digits can be found in the results directory:

```
[root@bright91 ~]# ls results/
reconstruction_10.png reconstruction_4.png reconstruction_8.png sample_2.png sample_6.png
reconstruction_1.png reconstruction_5.png reconstruction_9.png sample_3.png sample_7.png
reconstruction_2.png reconstruction_6.png sample_10.png sample_4.png sample_8.png
reconstruction_3.png reconstruction_7.png sample_1.png sample_5.png sample_9.png
```